

SafePack LM XP-N



The **SafePack LM XP-N** series meets the technical demands required for the production of food cosmetics, healthcare, pharmaceutical and tobacco packaging in offset printing.

The SafePack LM XP-N series are very low odour, low swelling and low migration.

The selection of the raw material for the series **SafePack LM XP-N** is effected according to the EuPIA selection list. The requirements of scent reduction calls for binding agents which do not comply with the common demands for rub resistance. Therefore dispersion varnishing is strictly necessary for all printing jobs with **SafePack LM XP-N**. The responsibility for the use and the proof for the conformity of the manufactured packaging are as legally stipulated in the competence of the print shop.

Properties:

Low odour:	yes
Low swelling:	yes
Low migration:	yes

All requirements towards the total migration (< 60 ppm) as well as towards the specific migration (<10 ppb) for non-evaluated substances can be fulfilled.

Free of mineral oil:	yes
Setting:	yes
Drying:	purely drying by absorption
Primary food packaging:	suitable
Dispersion varnishing:	necessary

			Light	Transp.	Sprit	Nitro	Alkali
SafePack LM XP-N	Yellow	(AW04CF7300Y.2)	5	+	+	+	+
SafePack LM XP-N	Magenta	(AW04CF7300M.2)	5	+	+	+	-
SafePack LM XP-N	Cyan	(AW04CF7300C.2)	8	+	+	+	+
SafePack LM XP-N	Black	(AW 04CF7300K.2)	8	-	+	+	+

+ Properties given, - Properties not given

This technical instruction sheet is designed for your information and reference. It is based on and conforms to our current knowledge. However as actual application is affected by many factors over which we have no control, we are not liable for printing failures.